

OTOMATIC

OTOMATIC Smolec i Wronka sp. jawna
32-652 Bulowice, ul. Krakowska 83
POLAND
VAT EU : PL 549 244 98 65

Chris Smolec tel. 0048 884-160-744



DPF Profit product description:

- hot water high-pressure device,
- uses the phenomenon of hydrodynamics of turbulent water flow, and the force of the compressed air pulse from the compressor,
- it works perfectly with DPF Active Matic cleaning agent reducing the surface tension of water, thanks to which the particles of the cleaning agent are more effective in removing dirt from the surface being cleaned,
- it cleanses particulate filters from soot, ashes and oils.

Intended use :

- DPF / FAP / CAT / and SCR removable inserts
- passenger cars, vans, bus and lorries

Technical parameters – DPF Profit:

- **400 V supply voltage:**
water pump
water heaters
air blower
- **tank :** 180 l
- **control panel :** colored touch screen
- **back pressure test before and after cleaning (mbar):**
- **air flow rate test 0 – 100%**
- **printing cleaning efficiency reports:**
online report generator (partner zone)
- **drying system:**
1 level, inside the machine, air blower
- **parameters of the cooperating compressor:** up to 10 bar (not included)
- **dirty water filtration system:** internal, integrated with the machine (2 filtration tanks)
- **installation of a diesel particulate filter – passenger car:** pneumatic quick coupler
- **installation of a diesel particulate filter – lorries:** connection adapter
- **type of material used:** stainless steel
- **external dimensions of the cabin (height x width x depth):** 230×120×100 cm (without filtration tanks and control panel)

DPF System plus product description:

- specialized device for drying and testing DPF / FAP / CAT filters
- uses the force of the air flow from the side channel blower and high temperature of compressed air
- thanks to the pressure transducer, it is ideally suited as a measuring device

Intended use :

- DPF / FAP / CAT / and SCR removable inserts
- passenger cars, vans, bus and lorries

Functions :

- testing
- drying
- printing reports

Technical parameters – DPF System plus:

- **400 V supply voltage:**
air blower 3 KW
air flow max 219m³/h
pressure max 350 mbar
- **control panel:** key panel
- **back pressure test before and after cleaning (mbar):**
- **printing cleaning efficiency reports:**
online report generator (partner zone)
printer in the machine
- **drying system :**
side channel blower
- **parameters of the cooperating compressor:** up to 10 bar (not included)
- **installation of a diesel particulate filter – passenger car:** pneumatic quick coupler
- **type of material used:** stainless steel

The DPF Profit duo set contains:

- DPF system plus and DPF Profit cleaning machine
- set of connection adapters for particulate filters (cars, vans and lorries)
- endoscope – mini USB inspection camera
- a set of cartridges for the dirty water filtration system
- cleaning agent (2 x 5l)
- specialist pen for steel filter housing
- training

Set price and financial settlement:

- **Net price: 24.000 GBP (only for EU valid VAT number)**
- **I payment** in the amount of 8.000 GBP, payable up to 7 days from the date of order
- **II payment** in the amount of 16.000 GBP, payable at the latest on delivery of the goods