

OTOMATIC

OTOMATIC Smolec i Wronka sp. jawna
32-652 Bulowice, ul. Krakowska 83
POLAND
VAT EU : PL 549 244 98 65

Chris Smolec tel. 0048 884-160-744



Product description:

- specialized device for drying and testing DPF / FAP / CAT filters
- uses the force of the air flow from the side channel blower and high temperature of compressed air
- thanks to the pressure transducer, it is ideally suited as a measuring device

Intended use :

- DPF / FAP / CAT / and SCR removable inserts
- passenger cars, vans, bus and lorries

Functions :

- testing
- drying
- printing reports

Technical parameters – DPF System plus:

- **400 V supply voltage:**
air blower 3 KW
air flow max 219m³/h
pressure max 350 mbar
- **control panel:** key panel
- **back pressure test before and after cleaning (mbar):**
- **printing cleaning efficiency reports:**
online report generator (partner zone)
printer in the machine
- **drying system :**
side channel blower
- **parameters of the cooperating compressor:** up to 10 bar (not included)
- **installation of a diesel particulate filter – passenger car:** pneumatic quick coupler
- **type of material used:** stainless steel

The DPF System plus set contains:

- DPF System plus machine
- set of connection adapters for particulate filters (cars, vans and lorries)
- endoscope – mini USB inspection camera
- specialist pen for steel filter housing
- training

Set price and financial settlement:

- **Net price: 7.400 GBP (only for EU valid VAT number)**
- **I payment** in the amount of 2.200 GBP, payable up to 7 days from the date of order
- **II payment** in the amount of 5.200 GBP, payable at the latest on delivery of the goods